

SAFETY DATA SHEET

According to Regulation (EU) No 1907/2006 (Reach) Annex

PRODUCT NAME : R-417A
 OTHER NAME : Butane, Pentafluoroethane, 1,1,1,2-Tetrafluoroethane
 USE : Refrigerant Gas
 SUPPLIER : Global Refrigerants (s) PTE. LTD.
 9 TUAS LINK 1, SINGAPORE 638587

2) HAZARDS IDENTIFICATION

CLASSIFICATION : Gases under pressure, Liquefied Gas
 SIGNAL WORD : WARNING
 HAZARD STATEMENT : H280/EUH044 Contains gas under pressure, may explode if heated
 SYMBOL : Gas Cylinder
 STORAGE STATEMENT : P410-P403 Protect from sunlight, store in a well-ventilated place



EMERGENCY OVERVIEW: Colourless, volatile liquid with ethereal and faint sweetish odour. Non-flammable material. Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapours displace air and can cause asphyxiation in confined spaces. At higher temperatures, (>250°C), decomposition products may include Hydrofluoric Acid (HF) and carbonyl halides.

POTENTIAL HEALTH HAZARDS

SKIN : Irritation would result from a defatting action on tissue. Liquid contact could cause frostbite.

EYES: Liquid contact can cause severe irritation and frostbite. Mist may irritate.

INHALATION : R-417A is low in acute toxicity in animals. When oxygen levels in air are reduced to 12-14% by displacement, symptoms of asphyxiation, loss of coordination, increased pulse rate and deeper respiration will occur. At high levels, cardiac arrhythmia may occur.

INGESTION: Ingestion is unlikely because of the low boiling point of the material. Should it occur, discomfort in the gastrointestinal tract from rapid evaporation of the material and consequent evolution of gas would result. Some effects of inhalation and skin exposure would be expected.

DELAYED EFFECTS : None (not known)

3) COMPOSITION / INFORMATION ON INGREDIENTS

| INGREDIENT NAME | CAS NUMBER | WEIGHT % |
|--------------------------------------|------------|----------|
| Butane (HC 600) | 106-97-8 | 3.4 |
| Pentafluoroethane (HFC-125) | 354-33-6 | 46.6 |
| 1,1,1,2-Tetrafluoroethane (HFC-134a) | 811-97-2 | 50 |

There are no impurities or stabilizers that contribute to the classification of the material identified in Section 2

4) FIRST AID MEASURES

SKIN: Promptly flush skin with water until all chemical is removed. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. Get medical attention if symptoms persist.

EYES: Immediately flush eyes with large amounts of water for at least 15 minutes (in case of frostbite, water should be lukewarm, not hot) lifting eyelids occasionally to facilitate irrigation. Get medical attention if symptoms persist.

INHALATION: Immediately move to fresh air. If breathing has stopped, give artificial respiration. Use oxygen as required, provided a qualified operator is available. Get medical attention immediately. DO NOT give epinephrine (adrenaline).

INGESTION: Ingestion is unlikely because of the physical properties and is not expected to be hazardous. DO NOT induce vomiting unless instructed to do so by a physician.

ADVICE TO PHYSICIAN: Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

5) FIRE FIGHTING MEASURES**FLAMMABLE PROPERTIES**

FLASH POINT : Gas, not applicable per DOT regulations

FLASH POINT METHOD : Not applicable

AUTOIGNITION TEMPERATURE : Unknown

UPPER FLAME LIMIT (volume % in air) : None*

LOWER FLAME LIMIT (volume % in air) : None*

*Based on ASHRAE Standard 34 with match ignition

FLAME PROPAGATION RATE (solids) : Not applicable

OSHA FLAMMABILITY CLASS : Not applicable

EXTINGUISHING MEDIA

Use any standard agent – choose the one most appropriate for type of surrounding fire (material itself is not flammable)

UNUSUAL FIRE AND EXPLOSION HAZARDS:

R-417A is not flammable at ambient temperatures and atmospheric pressure. However, this material will become combustible when mixed with air under pressure and exposed to strong ignition sources. Contact with certain reactive metals may result in formation of explosive or exothermic reactions under specific conditions (e.g. very high temperatures and/or appropriate pressures).

SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:

Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool.

6) ACCIDENTAL RELEASE MEASURESIN CASE OF SPILL OR OTHER RELEASE:

(Always wear recommended personal protective equipment.) Evacuate unprotected personnel. Product dissipates upon release. Protected personnel should remove ignition sources and shut off leak, if without risk, and provide ventilation. Unprotected personnel should not return to the affected area until air has been tested and determined safe, including low-lying areas.

Spills and releases may have to be reported to local authorities. See also Section 15 regarding reporting requirements.

7) HANDLING AND STORAGENORMAL HANDLING:

(Always wear recommended personal protective equipment.) Avoid breathing vapours and liquid contact with eyes, skin or clothing. Do not puncture or drop cylinders, expose them to open flame or excessive heat. Use authorized cylinders only. Follow standard safety precautions for handling and use of compressed gas cylinders.

R-417A should not be mixed with air above atmospheric pressure for leak testing or any other purpose.

STORAGE RECOMMENDATIONS:

Store in a cool, well-ventilated area of low fire risk and out of direct sunlight. Protect cylinder and its fittings from physical damage. Storage in subsurface locations should be avoided. Close valve tightly after use and when empty.

INCOMPATIBILITIES:

Freshly abraded aluminium surfaces at specific temperatures and pressures may cause a strong exothermic reaction. Chemically reactive metals: potassium, calcium, powdered aluminium, magnesium, and zinc.

8) EXPOSURE CONTROLS / PERSONAL PROTECTIONENGINEERING CONTROLS:

Provide local ventilation at filling zones and areas where leakage is probable. Mechanical (general) ventilation may be adequate for other operating and storage areas.

PERSONAL PROTECTIVE EQUIPMENT

SKIN PROTECTION: Skin contact with refrigerant may cause frostbite. General work clothing and gloves (leather) should provide adequate protection. If prolonged contact with liquid or gas is anticipated, insulated gloves constructed of PVA, neoprene or butyl rubber should be used. Any contaminated clothing should be promptly removed and washed before reuse.

EYE PROTECTION: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear chemical safety goggles.

RESPIRATORY PROTECTION: None generally required for adequately ventilated work situations. For accidental release or non-ventilated situations, or release into confined space, where the concentration may be above the PEL of 1,000 ppm, use a self-contained, NIOSH approved breathing apparatus or supplied air respirator. For escape: use the former or a NIOSH approved gas mask with organic vapor canister.

ADDITIONAL RECOMMENDATIONS: Where contact with liquid is likely, such as in a spill or leak, impervious boots and clothing should be worn. High dose-level warning signs are recommended for areas of principle exposure. Provide eyewash stations and quick drench shower facilities at convenient locations.

EXPOSURE GUIDELINES :

| <u>INGREDIENT NAME</u> | <u>ACGIH TLV</u> | <u>OSHA PEL</u> | <u>OTHER LIMIT</u> |
|---------------------------|------------------|-----------------|---------------------|
| Tetrafluoroethane 1,1,1,2 | None | None | *1000 ppm TWA (8hr) |
| Pentafluoroethane | None | None | *1000 ppm TWA (8hr) |
| Butane | None | None | *600 ppm TWA (8hr) |

* = Workplace Environmental Exposure Level (AIHA)

OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:

Hydrogen Fluoride: ACGIH TLV: 2 ppm ceiling, 0.5 ppm TLV-TWA

9) PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------|-------------------------------------|
| APPEARANCE | : Clear, colorless liquid and vapor |
| PHYSICAL STATE | : Gas at ambient temperatures |
| MOLECULAR WEIGHT | : unknown |
| ODOR | : Faint ethereal odor |
| SPECIFIC GRAVITY (water = 1.0) | : unknown |
| SOLUBILITY IN WATER (weight %) | : Unknown |
| pH | : Neutral |
| BOILING POINT | : -39.1°C |
| FREEZING POINT | : Not Determined. |

| | | | |
|-----------------------------------|---|----------------------------------|--------------------|
| VAPOR PRESSURE | : | 156.2 psia @ 70°F | 356.7 psia @ 130°F |
| VAPOR DENSITY (air = 1.0) | : | 3 | |
| EVAPORATION RATE | : | >1 COMPARED TO: CCl ₄ | = 1 |
| % VOLATILES | : | 100 | |
| ODOR THRESHHOLD | : | Not established | |
| FLAMMABILITY | : | Not applicable | |
| LEL/UEL | : | None/None | |
| RELATIVE DENSITY | : | 1.16g/cm ³ at 21.1°C | |
| PARTITION COEFF (n-octanol/water) | : | Not Applicable | |
| AUTO IGNITION TEMP | : | Not determined | |
| DECOMPOSITION TEMPERATURE | : | >250°C | |
| VISCOSITY | : | Not applicable | |
| FLASH POINT | : | Not applicable | |

10) STABILITY AND REACTIVITY

NORMALLY STABLE (CONDITIONS TO AVOID): The product is stable. Do not mix with oxygen or air above atmospheric pressure. Any source of high temperatures, such as lighted cigarettes, flames, hot spots or welding may yield toxic and/or corrosive decomposition products.

INCOMPATIBILITIES: (Under specific conditions: e.g. very high temperatures and/or appropriate pressures) – Freshly abraded aluminium surfaces (may cause strong exothermic reaction). Chemically reactive metals: potassium, calcium, powdered aluminium, magnesium, and zinc.

HAZARDOUS DECOMPOSITION PRODUCTS: Halogens, halogen acids and possibly carbonyl halides.

HAZARDOUS POLYMERIZATION: Will not occur.

11) TOXICOLOGICAL INFORMATIONIMMEDIATE (ACUTE) EFFECTS:

HFC-125: LC50 : Inhalation 4 hr. (rat) - > 800,000 ppm / Cardiac Sensitization threshold (dog) 75,000 ppm

HFC-134a: LC50 : Inhalation 4hr. (rat) - > 500,000 ppm / Cardiac Sensitization threshold (dog) > 80,000 ppm

DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:

HFC-125: Teratogenic NOEL (rat and rabbit) – 50,000 ppm Subchronic inhalation (rat) NOEL - > 50,000 ppm / Chronic NOEL – 10,000 ppm

HFC-134a: Teratogenic NOEL (rat and rabbit) – 40,000 ppm Subchronic inhalation (rat) NOEL – 50,000 ppm / Chronic NOEL – 10,000 ppm

REPEATED DOSE TOXICITY:

Lifetime inhalation exposure of male rats was associated with a small increase in salivary gland fibrosarcomas.

OTHER DATA :

HC 600, HFC-125, HFC-134a: Not active in four genetic studies

FURTHER INFORMATION: Acute effects of rapid evaporation of the liquid may cause frostbite. Vapours are heavier than air and can displace oxygen causing difficulty breathing or suffocation. May cause cardiac arrhythmia.

POTENTIAL HEALTH HAZARDS

SKIN: Irritation would result from a defatting action on tissue. Liquid contact could cause frostbite.

EYES: Liquid contact can cause severe irritation and frostbite. Mist may irritate.

INHALATION: R-417A is low in acute toxicity in animals. When oxygen levels in air are reduced to 12-14% by displacement, symptoms of asphyxiation, loss of coordination, increased pulse rate and deeper respiration will occur. At high levels, cardiac arrhythmia may occur.

INGESTION: Ingestion is unlikely because of the low boiling point of the material. Should it occur, discomfort in the gastrointestinal tract from rapid evaporation of the material and consequent evolution of gas would result. Some effects of inhalation and skin exposure would be expected.

DELAYED EFFECTS: None known. Ingredients found on one of the OSHA designated carcinogen lists are listed below

| <u>INGREDIENT NAME</u> | <u>NTP STATUS</u> | <u>IARC STATUS</u> | <u>OSHA LIST</u> |
|------------------------|-------------------|--------------------|------------------|
|------------------------|-------------------|--------------------|------------------|

No ingredients listed in this section

12) ECOLOGICAL INFORMATION

Degradability (BOD) : R-417A is a gas at room temperature; therefore, it is unlikely to remain
In water.

Octanol Water Partition : Unknown
co-efficient

13) DISPOSAL CONSIDERATIONS

RCRA

SDS

Is the unused product a RCRA hazardous waste if discarded? : Not a hazardous waste
If yes, the RCRA ID number is : Not applicable

OTHER DISPOSAL CONSIDERATIONS:

Disposal must comply with local disposal or discharge laws. R-417A is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

14) TRANSPORT INFORMATION

UN No. : UN1078
PROPER SHIPPING NAME : Refrigerant Gas R 417A
HAZARD CLASS : 2.2
US DOT PACKING GROUP : N.A.

For additional information on shipping regulations affecting this material, contact the information number found in Section 1.

15) REGULATORY INFORMATION**TOXIC SUBSTANCES CONTROL ACT (TSCA)**

TSCA INVENTORY STATUS : Listed on the TSCA inventory
OTHER TSCA ISSUES : May contain 0-10 ppm Ethane, 2-chloro1,1,1-trifluoro,
CAS# 75-88-7

SARA TITLE III / CERCLA

"Reportable Quantities" (RQs) and/or "Threshold Planning Quantities" (TPQs) exist for the following ingredients.

| <u>INGREDIENT NAME</u> | <u>SARA / CERCLA RQ (lb.)</u> | <u>SARA EHS TPQ (lb.)</u> |
|---------------------------------------|-------------------------------|---------------------------|
| No ingredients listed in this section | | |

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to your Local Emergency Planning Committee.

SECTION 311 HAZARD CLASS : IMMEDIATE PRESSURE

SARA 313 TOXIC CHEMICALS:

The following ingredients are SARA 313 "Toxic Chemicals". CAS numbers and weight percentages are found in Section 2.

| <u>INGREDIENT NAME</u> | <u>COMMENT</u> |
|--|----------------|
| No ingredients listed in this section. | |

STATE RIGHT-TO-KNOW

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

| <u>INGREDIENT NAME</u> | <u>WEIGHT %</u> | <u>COMMENT</u> |
|---------------------------------------|-----------------|----------------|
| No ingredients listed in this section | | |

ADDITIONAL REGULATORY INFORMATION:

R-417A is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.

WARNING: DO NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered. Contains Butane (HC-600), Pentafluoroethane (HFC-125), & 1,1,1,2-Tetrafluoroethane (HFC-134a), a greenhouse gas which may contribute to global warming.

FOREIGN INVENTORY STATUS: EU - EINECS #2034487 – HC 600, # 2065578 – HFC-125, and # 223770 - HFC 134a

16) OTHER INFORMATION

CURRENT ISSUE DATE: January 3rd 2017

OTHER INFORMATION: HMIS Classification: Health – 1, Flammability – 1, Reactivity – 0
NFPA Classification: Health – 2, Flammability – 1, Reactivity – 0
ANSI/ASHRAE 34 Safety Group – A1

Regulatory Standards:

1. OSHA regulations for compressed gases: 29 CFR 1910.101
2. DOT classification per 49 CFR 172.101

Toxicity information per PAFT Testing

DISCLAIMER:

Global Refrigerants (s) Pte. Ltd. believes that the information and recommendations contained herein (including data and statements are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other methods of use of the product and of the information referred to herein are beyond the control of National Refrigerants. We also expressly disclaim any and all liability as to any results obtained or arising from any use of the product or reliance on such information.
